

STRIEM



MANUFACTURERS OF
OIL SEPARATORS | SOLIDS INTERCEPTORS | CHEMICAL WASTE TANKS

PRODUCT CATALOG NO. 6

A NOTE FROM TWO BROTHERS.



WE LOVE MAKING PLUMBING PRODUCTS.

We formed Striem in 2015 with one idea in mind: dealing with a manufacturer should be like a breath of fresh air. That's why we implemented a simple formula:

- ✓ Build quality products,
- ✓ Ship them on time, and
- ✓ Provide damn good customer service.

We hope you enjoy working with us.

VINCE ISMERT
Direct: 816-591-9765

GABE ISMERT
Direct: 816-820-5454

TABLE OF CONTENTS

OIL SEPARATORS

- OS series5
- Oil Tanker™ series7
- Slick Stick™ oil level monitoring system9

SOLIDS INTERCEPTORS

- Sidekick™ point-of-use side-access 12
- Aardvark™ basket-style 13
- Prospector™ screen-style 15
- Settler™ sand interceptors 16

CHEMICAL WASTE TANKS

- Lab Rat™ under counter neutralization tanks .. 18
- Lab Basin™ centralized neutralization tanks .. 19
- Command Center™ pH monitoring package .. 21
- Bio Basin™ decontamination tanks..... 22

SAMPLING PORT

- Inspector™ sampling port 23

ACCESSORIES

- Risers..... 24
- High water table hold down kits..... 25
- Covers..... 26



913-222-1500 HELP@STRIEMCO.COM STRIEMCO.COM


CUSTOMER SERVICE HOURS: 8 AM - 5 PM CST

OIL SEPARATORS



OT-500 being moved with built-in Lifting Lug Kit

STRIEM'S OIL SEPARATOR FOOTPRINT




● Represents jurisdiction with Striem oil separator installation(s) since 2016.


APPLICATIONS




AUTO SERVICE/
REPAIR STATIONS



FIRE HOUSE/
POLICE STATIONS



PARKING
GARAGES



HYDRAULIC
ELEVATOR PITS




CAR WASHES



LOADING
DOCKS



AIRPORTS /
HANGARS




OPTIONS

Covers

See page 26 for more details



H-20



C24-H
Traffic-rated bolted composite

C24-HP
H-20 rated pickable cast iron

SR/LR field-adjustable extensions

See page 24 for more details

16"



SR-16

24"



SR-24



LR-24



Corrugated Pipe Riser Kit (CPRK)

See page 24 for more details




High water table hold down kits

See page 25 for more details



Slick Stick™ oil level monitoring system

See page 9 for more details




OS-15

16"

CONNECTIONS: 2", 3"
MAX FLOW RATE: 15 GPM
LIQUID CAPACITY: 15 GAL.
OIL CAPACITY: 10 GAL.

SAND CAPACITY: 1 GAL.
WEIGHT: 28 LBS.
COVER: PEDESTRIAN-RATED




OS-25

16"

CONNECTIONS: 2", 3"
MAX FLOW RATE: 25 GPM
LIQUID CAPACITY: 21 GAL.
OIL CAPACITY: 15 GAL.

SAND CAPACITY: 6 GAL.
WEIGHT: 31 LBS.
COVER: PEDESTRIAN-RATED




OS-35

24"

CONNECTIONS: 2", 3", 4"
MAX FLOW RATE: 35 GPM
LIQUID CAPACITY: 38 GAL.
OIL CAPACITY: 28 GAL.

SAND CAPACITY: 6 GAL.
WEIGHT: 77 LBS.
COVER: PEDESTRIAN-RATED




OS-50

24"

TRAFFIC H-20 HDK SS

CONNECTIONS: 2", 3", 4"
MAX FLOW RATE: 50 GPM
LIQUID CAPACITY: 57 GAL.
OIL CAPACITY: 40 GAL.

SAND CAPACITY: 7 GAL.
WEIGHT: 92 LBS.
COVER: PEDESTRIAN-RATED



OS-75

24"

H-20 CPRK HDK SS

CONNECTIONS: 4", 6"
MAX FLOW RATE: 75 GPM
LIQUID CAPACITY: 110 GAL.
OIL CAPACITY: 93 GAL.

SAND CAPACITY: 11 GAL.
WEIGHT: 130 LBS.
COVER: TRAFFIC-RATED



OS-100

24"

H-20 CPRK HDK SS

CONNECTIONS: 4", 6"
MAX FLOW RATE: 100 GPM
LIQUID CAPACITY: 250 GAL.
OIL CAPACITY: 144 GAL.

SAND CAPACITY: 95 GAL.
WEIGHT: 230 LBS.
COVER: TRAFFIC-RATED



(OT-500 shown)

OPTIONS

Risers

See page 24 for more details

24" SR/LR field-adjustable extensions



CPRK Corrugated Pipe Riser Kit (CPRK)




HDK High water table hold down kits

See page 25 for more details



SS Slick Stick™ oil level monitoring system


See page 9 for more details



OT-500

24" CPRK HDK SS


CONNECTIONS: 4", 6", 8" SAND CAPACITY: 162 GAL.
MAX FLOW RATE: 314 GPM WEIGHT: 1,000 LBS.
LIQUID CAPACITY: 560 GAL. COVER: CAST IRON (H-20)
OIL CAPACITY: 285 GAL.



OT-750

24" CPRK HDK SS


CONNECTIONS: 4", 6", 8" SAND CAPACITY: 295 GAL.
MAX FLOW RATE: 314 GPM WEIGHT: 1,200 LBS.
LIQUID CAPACITY: 750 GAL. COVER: CAST IRON (H-20)
OIL CAPACITY: 323 GAL.



OT-1000

24" CPRK HDK SS

CONNECTIONS: 4", 6", 8" SAND CAPACITY: 477 GAL.
MAX FLOW RATE: 314 GPM WEIGHT: 1,450 LBS.
LIQUID CAPACITY: 1,000 GAL. COVER: CAST IRON (H-20)
OIL CAPACITY: 370 GAL.




OT-1500

24" CPRK HDK SS

CONNECTIONS: 4", 6", 8" SAND CAPACITY: 825 GAL.
MAX FLOW RATE: 314 GPM WEIGHT: 1,600 LBS.
LIQUID CAPACITY: 1,500 GAL. COVER: CAST IRON (H-20)
OIL CAPACITY: 488 GAL.

SLICK STICK™





Control panel & float switch



Cover adapter with conduit connection & junction box



SLICK STICK™ INSTALLATION WITH RISER



Pictured: OS-75-SS

MODELS

- OS-50-SS
- OS-75-SS
- OS-100-SS
- OT-500-SS
- OT-750-SS
- OT-1000-SS
- OT-1500-SS

FEATURES

- UL listed
- Intrinsically safe
- Field-extendable interface float
- Ability to easily install with risers
- Audio and visual alarm
- BMS capability

SPECIFICATIONS

- Provides audio/visual alarm under high oil level condition
- Single phase, 120 VAC, 60 hertz input power required
- NEMA 4X enclosure
- "HORN OFF" button silences audible alarm
- "TEST" button tests system electronics
- Locking clasp on door
- Intrinsically safe sensor inputs
- Interface float is buoyant in water, but sinks in the presence of hydrocarbons

SOLIDS INTERCEPTORS





The Sidekick installed under a break room sink

POINT-OF-USE SIDE-ACCESS SOLIDS INTERCEPTOR

SIDEKICK™

UPC
List by IAPMO to IGC 167-2011ae2
Pat No. 10,786,761

NEW PRODUCT



APPLICATIONS



LAUNDRY FACILITIES



COMMERCIAL KITCHENS




DOG WASH & PET KENNELS



ART ROOM SINKS



BARBER SHOPS & HAIR SALONS



UTILITY SINKS

**BASKET-STYLE
SOLIDS INTERCEPTORS**

Recommended for DIY maintenance


AARDVARK™ SERIES

UPC
List by IAPMO to IGC 167-2011ae2
Pat No. 10,786,761

CHECK OUT OUR
**ONLINE
SIZING TOOL.**
For laundry facilities

RFA DWG PDF CSI
AVAILABLE ONLINE FOR ALL PRODUCTS

- Field-extendable PVC basket handle
- Field adjustable cover adapter up to 5". Risers available for deeper burials.
- Interlocking flange "hard pipes" inlet pipe to basket
- All-perforated removable basket
- Polyethylene tank reinforced for above or below-grade installation
- Locking pin allows for easy handle removal during maintenance
- 2" sewer gas seal (movable between high or low outlet)
- Built-in high and low outlet
- Cap for unused outlet
- Handles allow for easy maintenance and serve as no-go's so that basket can only be inserted in one orientation




(AA-M shown)

OPTIONS

SR/LR field-adjustable extensions

See page 24 for more details




HDK High water table hold down kits

See page 25 for more details



Covers

See page 26 for more details



AA-S SMALL 16"

CONNECTIONS: 2", 3"
MAX FLOW RATE: 35 GPM
LIQUID CAPACITY: 16 GAL. (high outlet), 4 GAL. (low outlet)
SOLIDS CAPACITY: 2 GAL.
WEIGHT: 42 LBS.
COVER: PEDESTRIAN-RATED



AA-M MEDIUM 24"

CONNECTIONS: 3", 4"
MAX FLOW RATE: 50 GPM
LIQUID CAPACITY: 38 GAL. (high outlet), 12 GAL. (low outlet)
SOLIDS CAPACITY: 6 GAL.
WEIGHT: 83 LBS.
COVER: PEDESTRIAN-RATED



AA-L LARGE 24" HDK TRAFFIC H-20

CONNECTIONS: 3", 4"
MAX FLOW RATE: 75 GPM
LIQUID CAPACITY: 57 GAL. (high outlet), 14 GAL. (low outlet)
SOLIDS CAPACITY: 8 GAL.
WEIGHT: 105 LBS.
COVER: PEDESTRIAN-RATED



AA-XL EXTRA LARGE 24" HDK H-20

CONNECTIONS: 4", 6"
MAX FLOW RATE: 100 GPM
LIQUID CAPACITY: 110 GAL. (high outlet), 30 GAL. (low outlet)
SOLIDS CAPACITY: 10 GAL.
WEIGHT: 143 LBS.
COVER: TRAFFIC-RATED

APPLICATIONS



LAUNDRY FACILITIES



COMMERCIAL KITCHENS



DOG WASH & PET KENNELS



ART ROOM SINKS



BARBER SHOPS & HAIR SALONS



FOOD PROCESSING




**SCREEN-STYLE
SOLIDS INTERCEPTORS**

Recommended for professional pumper maintenance


PROSPECTOR™ SERIES



PS-15-S 16"
CONNECTIONS: 2", 3" **SOLIDS CAPACITY:** 7 GAL.
MAX FLOW RATE: 15 GPM **WEIGHT:** 30 LBS.
LIQUID CAPACITY: 15 GAL. **COVER:** PEDESTRIAN-RATED



PS-25-S 16"
CONNECTIONS: 2", 3" **SOLIDS CAPACITY:** 10 GAL.
MAX FLOW RATE: 25 GPM **WEIGHT:** 35 LBS.
LIQUID CAPACITY: 21 GAL. **COVER:** PEDESTRIAN-RATED



PS-35-S 24"
CONNECTIONS: 2", 3", 4" **SOLIDS CAPACITY:** 19 GAL.
MAX FLOW RATE: 35 GPM **WEIGHT:** 83 LBS.
LIQUID CAPACITY: 38 GAL. **COVER:** PEDESTRIAN-RATED



PS-50-S 24" HDK TRAFFIC H-20
CONNECTIONS: 2", 3", 4" **SOLIDS CAPACITY:** 29 GAL.
MAX FLOW RATE: 50 GPM **WEIGHT:** 100 LBS.
LIQUID CAPACITY: 57 GAL. **COVER:** PEDESTRIAN-RATED




PS-125-S 24" HDK H-20
CONNECTIONS: 4", 6" **SOLIDS CAPACITY:** 55 GAL.
MAX FLOW RATE: 75 GPM **WEIGHT:** 140 LBS.
LIQUID CAPACITY: 110 GAL. **COVER:** TRAFFIC-RATED



PS-275-S 24" HDK H-20
CONNECTIONS: 4", 6" **SOLIDS CAPACITY:** 210 GAL.
MAX FLOW RATE: 100 GPM **WEIGHT:** 270 LBS.
LIQUID CAPACITY: 250 GAL. **COVER:** TRAFFIC-RATED

**SAND
INTERCEPTORS**

SETTLER™ SERIES



CB-50-S 24" HDK H-20
CONNECTIONS: 3", 4" **SOLIDS CAPACITY:** 25 GAL.
MAX FLOW RATE: 50 GPM **WEIGHT:** 92 LBS.
LIQUID CAPACITY: 57 GAL. **COVER:** TRAFFIC-RATED



CB-50-G 24" HDK
CONNECTIONS: 3", 4" **SOLIDS CAPACITY:** 25 GAL.
MAX FLOW RATE: 50 GPM **WEIGHT:** 187 LBS.
LIQUID CAPACITY: 57 GAL. **COVER:** CAST IRON GRATE



CB-125-S 24" HDK H-20 CPRK
CONNECTIONS: 4", 6" **SOLIDS CAPACITY:** 70 GAL.
MAX FLOW RATE: 75 GPM **WEIGHT:** 130 LBS.
LIQUID CAPACITY: 110 GAL. **COVER:** TRAFFIC-RATED




CB-125-G 24" HDK
CONNECTIONS: 4", 6" **SOLIDS CAPACITY:** 70 GAL.
MAX FLOW RATE: 75 GPM **WEIGHT:** 213 LBS.
LIQUID CAPACITY: 110 GAL. **COVER:** CAST IRON GRATE



CB-275-S 24" HDK H-20 CPRK
CONNECTIONS: 4", 6" **SOLIDS CAPACITY:** 200 GAL.
MAX FLOW RATE: 100 GPM **WEIGHT:** 230 LBS.
LIQUID CAPACITY: 250 GAL. **COVER:** TRAFFIC-RATED

OPTIONS


SR/LR field-adjustable extensions
 See page 24 for more details



HDK High water table hold down kits
 See page 25 for more details



Covers
 See page 26 for more details



CPRK Corrugated Pipe Riser Kit (CPRK)
 See page 24 for more details




CHEMICAL WASTE TANKS



Striemsmiths Scott and Darrell building a neutralization tank

UNDER COUNTER NEUTRALIZATION TANKS

LAB RAT™ SERIES



LB-2

CONNECTIONS: 1.5", 2" **LIMESTONE LOAD:** 25 LBS.
LIQUID CAPACITY: 2 GAL. **WEIGHT:** 6 LBS.
of LAB SINKS: 1



LB-2-ADA


CONNECTIONS: 1.5", 2" **LIMESTONE LOAD:** 25 LBS.
LIQUID CAPACITY: 2 GAL. **WEIGHT:** 10 LBS.
of LAB SINKS: 1



LB-5


CONNECTIONS: 1.5", 2" **LIMESTONE LOAD:** 50 LBS.
LIQUID CAPACITY: 5 GAL. **WEIGHT:** 11 LBS.
of LAB SINKS: 2

APPLICATION LAYOUTS



LAB SINK

4" PVC pipe for support cut to size (by others)




LAB SINK

CENTRALIZED
NEUTRALIZATION TANKS


LAB BASIN™ SERIES




LB-15 16" LS CC-1
CONNECTIONS: 2", 3" **LIMESTONE LOAD:** 200 LBS.
LIQUID CAPACITY: 15 GAL. **WEIGHT:** 28 LBS.
OF LAB SINKS: 4 **COVER:** PEDESTRIAN-RATED




LB-25 16" LS CC-1
CONNECTIONS: 2", 3" **LIMESTONE LOAD:** 300 LBS.
LIQUID CAPACITY: 21 GAL. **WEIGHT:** 31 LBS.
OF LAB SINKS: 6 **COVER:** PEDESTRIAN-RATED



LB-500 24" LS HDK CC-1 CPRK
CONNECTIONS: 4", 6", 8" **LIMESTONE LOAD:** 4,250 LBS.
LIQUID CAPACITY: 500 GAL. **WEIGHT:** 750 LBS.
OF LAB SINKS: 150 **COVER:** TRAFFIC-RATED



LB-750 24" LS HDK CC-1 CPRK
CONNECTIONS: 4", 6", 8" **LIMESTONE LOAD:** 9,800 LBS.
LIQUID CAPACITY: 750 GAL. **WEIGHT:** 1,200 LBS.
OF LAB SINKS: 215 **COVER:** TRAFFIC-RATED




LB-35 24" LS CC-1
CONNECTIONS: 2", 3", 4" **LIMESTONE LOAD:** 450 LBS.
LIQUID CAPACITY: 38 GAL. **WEIGHT:** 77 LBS.
OF LAB SINKS: 9 **COVER:** PEDESTRIAN-RATED



LB-50 24" LS TRAFFIC HDK CC-1
CONNECTIONS: 2", 3", 4" **LIMESTONE LOAD:** 650 LBS.
LIQUID CAPACITY: 57 GAL. **WEIGHT:** 92 LBS.
OF LAB SINKS: 15 **COVER:** PEDESTRIAN-RATED




LB-1000 24" LS HDK CC-1 CPRK
CONNECTIONS: 4", 6", 8" **LIMESTONE LOAD:** 13,000 LBS.
LIQUID CAPACITY: 1,000 GAL. **WEIGHT:** 1,400 LBS.
OF LAB SINKS: 260 **COVER:** TRAFFIC-RATED



LB-1500 24" LS HDK CC-1 CPRK
CONNECTIONS: 4", 6", 8" **LIMESTONE LOAD:** 19,500 LBS.
LIQUID CAPACITY: 1,500 GAL. **WEIGHT:** 1,700 LBS.
OF LAB SINKS: 375 **COVER:** TRAFFIC-RATED




LB-125 24" LS HDK CC-1 CPRK
CONNECTIONS: 3", 4", 6" **LIMESTONE LOAD:** 1,550 LBS.
LIQUID CAPACITY: 110 GAL. **WEIGHT:** 130 LBS.
OF LAB SINKS: 35 **COVER:** TRAFFIC-RATED




LB-275 24" LS HDK CC-1 CPRK
CONNECTIONS: 3", 4", 6" **LIMESTONE LOAD:** 3,150 LBS.
LIQUID CAPACITY: 250 GAL. **WEIGHT:** 230 LBS.
OF LAB SINKS: 75 **COVER:** TRAFFIC-RATED

OPTIONS

SR/LR field-adjustable extensions
 See page 24 for more details



Covers
 See page 26 for more details



CPRK Corrugated Pipe Riser Kit (CPRK)
 See page 24 for more details



HDK High water table hold down kits
 See page 25 for more details




CC-1 Command Center™ pH Monitoring System
 See page 21 for more details





Clear front panel

Touchscreen interface




SPECIFICATIONS

- BMS Capability via ethernet connection
- Pre-programmed audio/visual alarm set points
- 3.5" color touchscreen display
- Storage: Includes (2), 1-year micro SD cards
- Pre-programmed with digital output to power solenoid valve for fresh water to flush if PH approaches high/low limits
- Nema 4x lockable weather proof enclosure -32°F to 122°F
- 120V AC power supply required




BB-275 24" HDK CPRK

CONNECTIONS: 2", 3", 4", 6"
LIQUID CAPACITY: 250 GAL.
WEIGHT: 230 LBS.
COVER: TRAFFIC-RATED




BB-500 24" HDK CPRK

CONNECTIONS: 2", 3", 4", 6"
LIQUID CAPACITY: 500 GAL.
WEIGHT: 750 LBS.
COVER: TRAFFIC-RATED




BB-750 24" HDK CPRK

CONNECTIONS: 2", 3", 4", 6"
LIQUID CAPACITY: 750 GAL.
WEIGHT: 1,200 LBS.
COVER: TRAFFIC-RATED



BB-1000 24" HDK CPRK

CONNECTIONS: 2", 3", 4", 6"
LIQUID CAPACITY: 1,000 GAL.
WEIGHT: 1,400 LBS.
COVER: TRAFFIC-RATED



BB-1500 24" HDK CPRK

CONNECTIONS: 2", 3", 4", 6"
LIQUID CAPACITY: 1,500 GAL.
WEIGHT: 1,700 LBS.
COVER: TRAFFIC-RATED

MONITORING PACKAGES



LOW OUTLET VALVE PACKAGES AVAILABLE
 See product specifications at striemco.com.

Striem recommends the following steps for sizing a decontamination tank:

$$\left[\begin{array}{l} \text{Number of} \\ \text{Fixtures} \\ \text{(showers or} \\ \text{eyewash stations)} \end{array} \right] \times \left[\begin{array}{l} \text{Supply Line} \\ \text{Flow Rate of} \\ \text{Each Fixture} \end{array} \right] \times \left[\begin{array}{l} \text{Rinse Time} \\ \text{(15-20 minutes} \\ \text{typical)} \end{array} \right] = \text{SIZE OF} \\ \text{TANK IN} \\ \text{GALLONS}$$

Sizing Sample:

1. A hospital with two emergency showers, each with a 3/4" supply line carrying a flow rate of 9.96 GPM. 2 fixtures x 9.96 GPM = 19.92 GPM
2. 19.92 GPM x 15 minutes = 298.8 gallons
3. Select Bio Basin™ model BB-500 (500 liquid holding gallons)

OPTIONS

24" SR/LR field-adjustable extensions
 See page 24 for more details



HDK High water table hold down kits
 See page 25 for more details



CPRK Corrugated Pipe Riser Kit (CPRK)
 See page 24 for more details



INSPECTOR™

INSPECTOR-4

4" connections



INSPECTOR-6

6" connections



Narrowed inlet flow path for easy sampling

1/2" offset to create sample waterfall.



SPECIFICATIONS

- Unit supplied with built-in adapter for up to 2-1/2" of adjustability
- Additional riser(s) available for deeper burial depth
- Polyethylene construction
- Lightweight and easy to install
- Maximum operating temperature 140° F
- Highway rated (16,000 lb. load) bolted, gas/water tight composite cover. (H-20 cast iron available)

FIELD-ADJUSTABLE RISERS

SEE PRODUCT SPECIFICATIONS FOR RISER OPTIONS

SR-16

For use with tanks with 16" cover



SR-24

SHORT RISER

For use with tanks with 24" cover



LR-24

LONG RISER

For use with tanks with 24" cover



Tilt adapter up to 6.5° in all directions to match grade.



CPRK Corrugated Pipe Riser Kit

Uses 18" Inner Diameter ADS N-12 Dual Wall HDPE Pipe (by others)

More cost-effective for deeper burials and/or on tanks with multiple manways.




HIGH WATER TABLE HOLD DOWN KITS

HDK-2



Compatible with:
 OS-50, OS-75, OS-100, OS-500
 OS-50-SS, OS-75-SS, OS-100-SS
 AA-L, AA-XL-4, AA-XL-6
 PS-50-S, PS-125-S, PS-275-S
 CB-50-S, CB-125-S, CB-275-S
 CB-50-G, CB-125-G
 LB-50, LB-125, LB-275
 BB-275

HDK-500



Compatible with:
 OT-500, OT-500-SS

HDK-750



Compatible with:
 OT-750, OT-750-SS

HDK-1000



Compatible with:
 OT-1000, OT-1000-SS

HDK-1500



Compatible with:
 OT-1500, OT-1500-SS

HDK-CWT-500



Compatible with:
 BB-500, LB-500

HDK-1



Compatible with:
 OS-750, OS-1000, OS-1500
 LB-750, LB-1000, LB-1500
 BB-750, BB-1000, BB-1500

COVERS




C16-M



C24-M



C24-H



C24-HP

LOCATION:
DIAMETER:
TYPE:
LOAD RATING:

INDOOR
 16"
 BOLTED POLYPRO
 2,500 LBS.

INDOOR
 24"
 BOLTED COMPOSITE
 2,000 LBS.

INDOOR / OUTDOOR
 24"
 BOLTED COMPOSITE
 16,000 LBS.

OUTDOOR
 24"
 PICKABLE CAST IRON
 16,000 LBS. H-2O RATED

NOTES





 913-222-1500

 HELP@STRIEMCO.COM

 STRIEMCO.COM