

SPECIFICATIONS


- 1. 4"/6" Plain End inlet, 3" Plain End vents, H20 traffic-rated cast iron covers standard.
- 2. For 6" connections, cut and remove 4" fitting section. (See IO&M for more detail.)
- 3. Liquid holding capacity: 1000 gallons (133 cu. ft.).
- 4. Unit weight w/ standard covers: 1324 lbs.
- 5. Maximum operating temperature 140 °F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- 5. Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.

ENGINEER SPECIFICATION GUIDE



Striem decontamination tank model BB-1000 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. 4" inlet/outlet connections can be field-cut to create 6" inlet/outlet connections. Tank liquid holding capacity shall be 1000 gallons. Covers shall be H20 traffic-rated pickable cast iron.



TOP VIEW



SECTION B-B



SECTION A-A

PO IS NON-CANCELABLE
ORDER IS NON-RETURNABLE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

OPTIONS

Connection Options (Plain End Only)

Optional Outlet

☐ 4/6"

Riser Options

From Factory: 0" - 5"

- ☐ Up to 24": SR24 (3)
- ☐ Up to 39": LR24 (3)
- ☐ Up to 43": SR24 (6)
- ☐ Up to 58": SR24 (3) + LR24 (3)
- ☐ Up to 72": LR24 (6)
- ☐ Up to 90": SR24 (3) + LR24 (6)
- ☐ Up to 106": LR24 (9)

- OR -

☐ CPRK (3): 11" - 106" (See specification for more detail.)

Additional Options

- ☐ C24-M (3): 2,000 lbs. Rated Bolted Composite Covers
- ☐ HDK-5: High Water Table Hold Down Kit
- ☐ AVA-3: Single-Level Monitoring Package *
- ☐ AVA-4: Multi-Level Monitoring Package *

*Monitoring packages will raise covers by 3".

MODEL NUMBER: BB-1000

DESCRIPTION:

BIO BASIN™
POLYETHYLENE DECONTAMINATION TANK
1000 GALLON CAPACITY

DWG BY: ENG

DATE: 8/24/2026

REV: 3

SPECIFICATION SHEET

Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com

Made in the U.S.A

