SPECIFICATIONS

- 4" Plain End inlet, 2" Plain End vents standard.
- Liquid holding capacity: 250 Gallons.
- Unit weight: 225 lbs.
- 4. Maximum operating temperature 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- Cover placement allows full access to tank for proper maintenance.

ENGINEER SPECIFICATION GUIDE

Striem decontamination tank model BB-275 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Tank liquid holding capactly shall be 250 gallons. Covers shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.


THIRD PARTY STRUCTURAL ANALYSIS

The BB-275 has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.




TOP VIEW

Finished Grade








MODEL NUMBER:

DESCRIPTION:



PO IS NON-CANCELABLE

ORDER IS NON-RETURNABLE

250 GALLON CAPACITY

BIO BASIN™

POLYETHYLENE DECONTAMINATION TANK

DWG BY: ENG DATE: 8/22/2023 **REV**:

BB-275

Striem **Kansas City, KS**

Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

SPECIFICATION SHEET

OPTIONS

Optional Outlet

2"

3"

6"

☐ CPRK (2): 11" - 90" (See specification for more detail.)

SELECTION

REQUIRED

Connection Options (Plain End Only)

Inlet

3"

4"

6"

- OR -

Riser Options

From Factory: Up to 5"

Up to 24": **SR24** (2)

☐ Up to 39": **LR24** (2)

Up to 43": **SR24** (4)

☐ Up to 72": **LR24** (4)

Additional Options

☐ Up to 58": **SR24** (2) + **LR24** (2)

☐ Up to 90": **SR24** (2) + **LR24** (4)

☐ **HDK-2:** High Water Table Hold Down Kit

■ AVA-3: Single-Level Monitoring Package*

■ AVA-4: Multi-Level Monitoring Package*

*Monitoring packages will raise covers by 3".