SPECIFICATIONS

- 1. 4" Plain End inlet shown, 2" Plain End pump outlet, 2" Plain End vents standard.
- 2. Liquid holding capacity: 250 Gallons
- 3. Unit weight: 225 Pounds
- 4. Maximum operating temperature 140°F continuous.

NOTES


- For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Cover placement allows full access to tank for proper maintenance.


ENGINEER SPECIFICATION GUIDE


Striem decontamination tank model BB-275-PP shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Tank liquid holding capacity shall be 250 gallons. Covers shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.

THIRD PARTY STRUCTURAL ANALYSIS


The BB-275-PP has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.







END VIEW



PO IS NON-**CANCELABLE RETURNABLE**

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

ORDER IS NON-

BIO BASIN™ POLYETHYLENE DECONTAMINATION TANK WITH PUMP PLATE 250 GALLON CAPACITY

DWG BY: ENG

MODEL NUMBER:

DESCRIPTION:

DATE:

7/25/2023

BB-275-PP

REV:

SPECIFICATION SHEET

OPTIONS

SELECTION

REQUIRED

CPRK (2): 11" - 87" (See specification for more detail.)

Connection Options (Plain End Only)

Inlet

2"

4"

□ 6"

- OR -

3"

Riser Options

From Factory: Up to 2"

Up to 21": **SR24** (2)

Up to 36": **LR24** (2)

Up to 40": **SR24** (4)

☐ Up to 69": **LR24** (4)

Additional Options

☐ Up to 55": **SR24** (2) + **LR24** (2)

☐ Up to 87": **SR24** (2) + **LR24** (4)

■ HDK-2: High Water Table Hold Down Kit

AVA-3: Single-Level Monitoring Package

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A

