#### **SPECIFICATIONS**

- 6" Plain End inlet shown, 3" Plain End vents standard.
- Liquid holding capacity: 500 gallons (66 cu. ft.).
- Unit weight: 800 lbs.
- 4. Maximum operating temperature 140°F continuous.

### **NOTES**


- 1. For gravity drainage applications only.
- Do not use for pressure applications.
- Cover placement allows full access to tank for proper maintenance.
- 4. Lifting lug set for easy install.

## **ENGINEER SPECIFICATION GUIDE**


Striem decontamination tank model BB-500 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustabe riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 500 gallons. Cover shall provide water/gastight seal and have a maximum 16,000 lbs. load capacity.


#### THIRD PARTY STRUCTURAL ANALYSIS

The structural design of the BB-500 has been approved and stamped by a third-party structural engineer for direct burial in accordance with Striem's installation instructions.










**TOP VIEW** 




# **SECTION A-A**

**MODEL NUMBER:** BB-500 **DESCRIPTION:** BIO BASIN™ POLYETHYLENE DECONTAMINATION TANK

**500 GALLON CAPACITY** 

Made in the U.S.A

Striem **Kansas City, KS** Tel: 913-222-1500 orders@striemco.com www.striemco.com



**OPTIONS** 

**SPECIFICATION SHEET** 

**DWG BY:** ENG

DATE:

8/25/2023

**REV**:

# PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.