



1. 3" Plain End inlet/outlet, 2" Plain End vents standard.
2. Liquid holding capacity: 21 Gallons.
3. Unit weight: 32 lbs.
4. Maximum operating temperature 140°F continuous.

1. For gravity drainage applications only.
2. Do not use for pressure applications.
3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
4. Cover placement allows full access to tank for proper maintenance.
5. Diptube is removable to inspect/clean piping.


Striem neutralization tank model LB-25 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 21 gallons. Cover shall provide water/gas-tight seal and have a maximum 450 lbs. load capacity when unit is installed above-grade, and 2,500 lbs. when buried with SR16 Riser.




TOP VIEW



END VIEW



SECTION A-A



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **STRIEM, LLC.**
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **STRIEM, LLC.** IS PROHIBITED.

Connection Options (Plain End Only)

☐ 2"

- ☐ **SR16 Riser:** 4"-16" Burial Range
- ☐ **CC-1 & SPK:** Command Center pH Monitoring Package with Sensor Placement Kit
- ☐ **Limestone:** 90%+ Calcium Carbonate (300 lbs.)

MODEL NUMBER:		LB-25	
DESCRIPTION:			
LAB BASIN™ POLYETHYLENE NEUTRALIZATION TANK			
DWG BY:	ENG	DATE:	8/25/2026
		REV:	0

SPECIFICATION SHEET

**Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com**

Made in the U.S.A

