SPECIFICATIONS

- 4" Plain End inlet/outlet, 2" Plain End vents, C24-M cover standard.
- Liquid holding capacity: 57 Gallons.
- 3. Unit weight: 93 lbs.
- 4. Maximum operating temperature 140°F continuous.

NOTES


- For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Cover placement allows full access to tank for proper maintenance.
- 4. Diptube is removable to inspect/clean piping.


ENGINEER SPECIFICATION GUIDE


Striem neutralization tank model LB-50 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 57 gallons. Cover shall provide water/gas-tight seal and have a maximum 2,000 lbs. load capacity.

THIRD PARTY STRUCTURAL ANALYSIS

The LB-50 has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.








MODEL NUMBER:

DWG BY: ENG

END VIEW

SECTION A-A



POLYETHYLENE NEUTRALIZATION TANK

DATE:

Made in the U.S.A

SPECIFICATION SHEET

OPTIONS

Connection Options (Plain End Only)

☐ **HDK-2**: High Water Table Hold Down Kit

■ SPK: Sensor Placement Kit*

☐ C24-H: Highway Rated Bolted Composite Cover

☐ **CC-1:** Command Center pH Monitoring Package

Limestone: 90%+ Calcium Carbonate (650 lbs.)

Inlet / Outlet

Riser Options

From Factory: 0" - 5"

☐ Up to 24": **SR24**

☐ Up to 39": **LR24**

*Required with CC-1

Additional Options

2"

3"

4"

DESCRIPTION: Striem Kansas City, KS LAB BASIN™ Tel: 913-222-1500 orders@striemco.com www.striemco.com

REV:

LB-50

5/24/2024