

SPECIFICATIONS


- 1. 4"/6" Plain End inlet/outlet, 3" Plain End vents standard.
- 2. For 6" connections, cut and remove 4" fitting section. (See IO&M for more details.)
- 3. Max flow rate: 314 GPM.
- 4. Liquid capacity: 750 gallons (100 cu. ft.).
- 5. Oil capacity: 323 gallons.
- 6. Solids capacity: 295 gallons.
- 7. Unit weight: 1253 lbs.
- 8. Maximum operating temperature 140 °F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- 5. Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.

ENGINEER SPECIFICATION GUIDE


Striem oil separator model OT-750 shall be lifetime guaranteed and made in the USA. Separator shall be constructed of polyethylene with 7/8" nominal wall thickness. Separator shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. 4" inlet/outlet connections can be field-cut to create 6" inlet/outlet connections. Separator flow rate shall be 314 GPM. Separator liquid holding capacity shall be 750 gallons and oil capacity shall be 323 gallons. Solids capacity shall be 295 gallons. Covers shall be H20 traffic-rated pickable cast iron. Separator shall be certified to IAPMO IGC 183-2016 and carry a UPC listing.



TOP VIEW



SECTION B-B



SECTION A-A

OPTIONS

Connection Options (Plain End Only)

Inlet / Outlet

☐ 8"

Riser Options

From Factory: Up to 5"

- ☐ Up to 24": SR24 (3)
- ☐ Up to 39": LR24 (3)
- ☐ Up to 43": SR24 (6)
- ☐ Up to 58": SR24 (3) + LR24 (3)
- ☐ Up to 72": LR24 (6)
- ☐ Up to 90": SR24 (3) + LR24 (6)
- ☐ Up to 106": LR24 (9)



- OR -

☐ CPRK (3): 11" - 106"

(See specification for more detail.)

Additional Options

- ☐ HDK-4: High Water Table Hold Down Kit
 - ☐ SS: Slick Stick™ Oil Level Monitoring System*
- *Monitoring system will raise covers by 3".



PO IS NON-CANCELABLE
ORDER IS NON-RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

MODEL NUMBER: OT-750

DESCRIPTION:

OIL TANKER™
POLYETHYLENE OIL SEPARATOR
750 GALLON CAPACITY

DWG BY: ENG

DATE: 7/21/2026

REV: 2

SPECIFICATION SHEET

Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com

Made in the U.S.A

