SPECIFICATIONS

- 2" Plain End inlet, 3" Plain End vents, C24-M cover standard.
- 2. Oil capacity: 57 Gallons (7.6 cu ft).
- Unit weight w/ standard cover: 93 lbs.; w/ cast iron cover: 153 lbs.
- 4. Maximum operating temperature: 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- Narrow footprint allows clearance through doorways and down stairs.
- 4. Cover placement allows full access to tank for proper maintenance.

ENGINEER SPECIFICATION GUIDE


Striem oil collection tank model OCT-50 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank oil collection capacity shall be 57 gallons. Cover shall provide water/gas-tight seal and have a maximum 2,000 lbs. load capacity.


THIRD PARTY STRUCTURAL ANALYSIS


The OCT-50 has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.



END VIEW







SECTION A-A



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

MODEL NUMBER: OCT-50 **DESCRIPTION:** 57 GALLON POLYETHYLENE **OIL COLLECTION TANK REV**:

DATE:

DWG BY: ENG

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A



5/19/2023