




Linwood Mining & Minerals Corp.

LIMESTONE, CALCIUM CARBONATE

SDS



LINWOOD MINING & MINERALS CORP.

401 EAST FRONT ST.
DAVENPORT, IA. 52804
PH: 563-324-1931 / 800-397-5463

Date of Preparation: 10/5/16
Updated: 12/14/20
Prepared for Striem
3100 Brinkerhoff Rd
Kansas City, KS 66115

Updated by: Mark Looman
Emergency Contact: Mark Looman 563-529-1063
Curt Shipman 563-529-9886
CHEMTREC Number: 800-424-9300

SECTION 1 : PRODUCT IDENTIFIER

Product Identifier: Limestone, Limestone/Dolomite, Dolomite, Calcium Carbonate, Calcium/Magnesium Carbonate, CaCO₃, CaCO₃/MgCO₃, Crushed Limestone, Granular Calcium Carbonate, Powder Calcium Carbonate, Chemical Grade Limestone

Other means of identification: Base and Surface Materials, Aggregates, Chemical Grade, Agricultural, Manufactured Sand, Rip-Rap, Feed Granulars, Granulars, Mineral Filler,

Recommended use of the chemical and restrictions on use: Limestone is used in the manufacture of bricks, mortar, cement, concrete, plasters, paving materials, other construction materials, steel, Glass Manufacturing, consumer products, and other goods. Limestone aggregate may be distributed in bags, totes, truck, rail, barge bulk shipments.

Recommended restrictions: None known.

SECTION 2 : HAZARD(S) IDENTIFICATION

Physical hazards: Not classified

Health Hazards: Carcinogenicity - Category 1A, Specific Target Organ Toxicity - Category 2, Repeated Exposure – Respiratory System

OSHA defined hazards: Not classified

Signal word: Danger



Linwood Mining & Minerals Corp.

Hazard statement:

May cause cancer. May cause damage to organs, (lung), through prolonged or repeated exposure.

Symbols



Precautionary statement: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Prevention: Wear protective gloves/protective clothing/eye protection/face protection.

Response: If exposed or concerned: Get medical advice/attention.

Storage: Restrict or control access to stockpile areas. Engulfment hazard: To prevent burial or suffocation, do not enter a confined space, such as a silo, bulk truck or other storage container or vessel that stores or contains aggregates without an effective procedure for assuring safety.

Disposal: Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) Not Otherwise Classified (HNOC): None known

Supplemental Information:

Respirable Crystalline Silica (RCS) may cause cancer. Limestone is a naturally occurring mineral complex that contains varying quantities of quartz (crystalline silica). In its natural bulk state, limestone is not a known health hazard. Limestone may be subjected to various natural or mechanical forces that produce small particles (dust) which may contain respirable crystalline silica (particles less than 10 micrometers in aerodynamic diameter). Repeated inhalation of respirable crystalline silica (quartz) may cause lung cancer according to IARC and NTP; ACGIH states that it is a suspected cause of cancer. Other forms of RCS (e.g., tridymite and cristobalite) may also be present or formed under certain industrial processes.



SECTION 3

COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name: Calcium Carbonate

Common name and synonyms: Limestone

CAS numbers and concentrations of ingredients:

Component	CAS #	% by weight
Calcium Carbonate	1317-65-3	55-100
Magnesium Carbonate	546-93-0	0-40
Crystalline Silica	14808-60-7	0 - 5

SECTION 4

FIRST AID MEASURES

Description of First Aid Measures:

Inhalation: Limestone dust: Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact: Limestone dust: Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact: Limestone dust: Immediately flush with plenty of water for at least 15 minutes. Hold eyelids apart. Occasionally lift the eyelid(s) to ensure thorough rinsing. Beyond flushing, do not attempt to remove material from the eye(s). Get medical attention if irritation develops or persists.

Ingestion: Limestone dust: Rinse mouth and drink plenty of water. Never give anything by mouth to an unconscious person. Get medical attention.

Most important symptoms/effects, both acute and delayed: Inhaling dust may cause discomfort in the chest, shortness of breath, and coughing. Prolonged inhalation may cause chronic health effects. This product contains crystalline silica. Prolonged or repeated inhalation of respirable crystalline silica liberated from this product can cause silicosis, and may cause cancer.

Indication of immediate medical attention and special treatment needed:

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information: Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Pre-existing medical conditions that may be aggravated by exposure include disorders of the eye, skin and lung (including asthma and other breathing disorders). If addicted to tobacco, smoking will impair the ability of the lungs to clear themselves of dust.



SECTION 5 FIRE FIGHTING MEASURES

Suitable extinguishing media: Limestone is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: None known

Specific hazards arising from the chemical: No unusual fire or explosion hazards noted. Not a combustible dust.

Special protective equipment and precautions for firefighters: Use protective equipment appropriate for surrounding materials.

No specific precautions: Contact with powerful oxidizing agents may cause fire and/or explosions (see section 10 of SDS).

General fire hazards: No unusual fire or explosion hazards noted.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions protective equipment and emergency procedures: Wear appropriate protective equipment and clothing during clean-up of materials that contain or may release limestone dust.

Methods and materials for containment and cleaning up: Spilled material, where dust is generated, may overexpose cleanup personnel to respirable crystalline silica-containing dust. Do not dry sweep or use compressed air for clean-up. Wetting of spilled material and/or use of respiratory protective equipment may be necessary.

Environmental precautions: Avoid discharge of fine particulate matter into drains or water courses.

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling: Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities: Avoid dust formation or accumulation.



SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational exposure limits:

- 1) Value equivalent to OSHA formulas (29 CFR 1910.1000; 29 CFR 1917; 29 CFR 1918)
- 2) Value also applies to MSHA Metal / Non-Metal (1973 TLVs at 30 CFR 56/57.5001)
- 3) OSHA enforces 0.250mg/m³ in construction and shipyards (CPL-03-00-007)
- 4) Value also applies to OSHA construction (29 CFR 1926.55 Appendix A) and shipyards (29 CFR 1915.1000, Table Z)
- 5) MSHA limit – 10 mg/m³

U.S. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Particulates not otherwise classified (CAS SEQ250).	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction Total dust (4)
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (4) Total dust (5)
Magnesium Carbonate (CAS 546-93-0)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (4) Total dust (5)

U.S. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Crystalline Silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m ³	Total dust (1,2)
		0.1 mg/m ³	Respirable (1,2,3)
Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)	TWA	0.15 mg/m ³ 0.05 mg/m ³	Total dust (1) Respirable (1,2)
Particulates not otherwise classified (CAS SEQ250)	TWA	5 mg/m ³ 15 mg/m ³	Respirable fraction (1) Total dust (1,4,5)

US. ACGIH Threshold Limit Values®

Components	Type	Value	Form
Crystalline Silica (all forms; CAS mixture)	TWA	0.025 mg/m ³	Respirable fraction
Particulates not otherwise classified silica) (CAS Mixture)	TWA	3 mg/m ³ 10 mg/m ³	Respirable particles (2) Inhalable particles (2)

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Crystalline Silica (all forms; CAS mixture)	TWA	0.05 mg/m ³	Respirable dust
Calcium Carbonate (CAS 1317-65-3)	TWA	5 mg/m ³	Respirable fraction



Linwood Mining & Minerals Corp.

Magnesium Carbonate (CAS 546-93-0)	TWA	10 mg/m ³	Total dust
		5 mg/m ³	Respirable fraction
		10 mg/m ³	Total dust

Biological limit values: No biological exposure limits noted for the ingredient(s).

Exposure guidelines: OSHA PELs, MSHA PELs, and ACGIH TLVs are 8-hr TWA values. NIOSH RELs are for TWA exposures up to 10-hr/day and 40-hr/wk. Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled. Terms including “Particulates Not Otherwise Classified,” “Particulates Not Otherwise Regulated,” “Particulates Not Otherwise Specified,” and “Inert or Nuisance Dust” are often used interchangeably; however, the user should review each agency’s terminology for differences in meanings.

Appropriate engineering controls: Good general ventilation (typically 10 air changes per hour indoors) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment:

Eye/face protection: Wear safety glasses with side shields (or goggles).

Skin protection: Use personal protective equipment as required.

Hand protection: Use personal protective equipment as required.

Other:

Respiratory protection: When handling or performing work with limestone that produces dust or respirable crystalline silica in excess of applicable exposure limits, wear a NIOSH-approved respirator that is properly fitted and is in good condition. Respirators must be used in accordance with all applicable workplace regulations.

Thermal hazards: Not anticipated. Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.



SECTION 9:	PHYSICAL AND CHEMICAL PROPERTIES
-------------------	---

Appearance:

Physical state: Solid

Form: Solid particles

Color: Grayish-white, Gray, Dark Gray, or Silver- Gray, Tan

Odor: Not applicable

Odor threshold: Not applicable.

pH: At 25⁰C 8.0-9.2

Melting point/freezing point: Not applicable

Initial boiling point and boiling range: Not applicable

Flash point: Non-combustible

Evaporation rate: Not applicable

Flammability (solid, gas): Not applicable

Upper/lower flammability or explosive limits Flammability limit – lower (%): Not applicable

Flammability limit – upper (%): Not applicable



Linwood Mining & Minerals Corp.

Vapor pressure: Not applicable

Vapor density: Not applicable

Relative density: Determined by Size

Solubility(ies):

Solubility (water): Insoluble

Partition coefficient (n-octanol/water): Not applicable

Auto-ignition temperature: Not applicable

Decomposition temperature: 725 – 890°C

Viscosity: Not applicable

Other information:

Explosive properties: Not applicable

Flammability: Not applicable

SECTION 10:	STABILITY AND REACTIVITY
--------------------	---------------------------------

Reactivity: The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability: Material is stable under normal conditions.



Linwood Mining & Minerals Corp.

Possibility of hazardous reactions: Not dangerous reaction known under conditions of normal use.

SECTION 11:	TOXICOLOGICAL INFORMATION
--------------------	----------------------------------

Information on likely routes of exposure:

Repeated inhalation of respirable crystalline silica (quartz) may cause silicosis, a fibrosis (scarring) of the lungs. Silicosis is irreversible and may be fatal. Silicosis increases the risk of contracting pulmonary tuberculosis. Some studies suggest that repeated inhalation of respirable crystalline silica may cause other adverse health effects including lung and kidney cancer.

Skin contact: Limestone dust: May cause irritation through mechanical abrasion.

Eye contact: Limestone dust: May cause irritation through mechanical abrasion.

Ingestion: Not likely, due to the form of the product. However, accidental ingestion of the content may cause discomfort.

Symptoms related to the physical, chemical and toxicological characteristics: Limestone dust: Discomfort in the chest. Shortness of breath. Coughing.

Information on toxicological effects:

Acute toxicity: Not expected to be acutely toxic.

Skin corrosion/irritation: This product is not expected to be a skin hazard.

Serious eye damage/eye irritation: Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization:

Respiratory sensitization: No respiratory sensitizing effects known.

Skin sensitization: Not known to be a dermal irritant or sensitizer.

Germ cell mutagenicity: No data available to indicate product or any components present at greater than 0.1% are mutagenic or Geno Toxic.



Linwood Mining & Minerals Corp.

Carcinogenicity: Respirable crystalline silica has been classified by IARC and NTP as a known human carcinogen, and classified by ACGIH as a suspected human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity:

Crystalline Silica (Quartz) (CAS 14808-60-7): 1 Carcinogenic to humans.

Respirable Tridymite and Cristobalite: 1 Carcinogenic to humans. (other forms of Crystalline) (CAS Mixture)

NTP Report on Carcinogens: Crystalline Silica (Quartz) (CAS 14808-60-7): Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed

Reproductive toxicity: Not expected to be a reproductive hazard.

Specific target organ toxicity - single exposure: Not classified.

Specific target organ toxicity – repeated exposure: Respirable crystalline silica: May cause damage to organs (lung) through prolonged or repeated exposure.

Aspiration hazard: Due to the physical form of the product it is not an aspiration hazard.

Chronic effects: Prolonged inhalation of respirable crystalline silica may be harmful. May cause damage to organs (lungs) through prolonged or repeated exposure. There are reports in the literature suggesting that excessive crystalline silica exposure may be associated with autoimmune disorders and other adverse health effects involving the kidney. In particular, the incidence of scleroderma (thickening of the skin caused by swelling and thickening of fibrous tissue) appears to be higher in silicotic individuals. To date, the evidence does not conclusively determine a causal relationship between silica exposure and these adverse health effects.

SECTION 12:	ECOLOGICAL INFORMATION
--------------------	-------------------------------

Eco toxicity: Not expected to be harmful to aquatic organisms. Discharging limestone dust and fines into waters may increase total suspended particulate (TSP) levels that can be harmful to certain aquatic organisms.

Persistence and degradability: Not applicable



Linwood Mining & Minerals Corp.

Bio accumulative potential: Not applicable

Mobility in soil: Not applicable

Other adverse effects: No other adverse environmental effects (e.g., ozone depletion, photochemical ozone creation potential, global warming potential) are expected from this component.

SECTION 13:	DISPOSAL CONSIDERATIONS
--------------------	--------------------------------

Disposal instructions: Do not allow fine particulate matter to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with fine particulates. Dispose of contents in accordance with local/regional/national/international regulations.

Hazardous waste code: Not regulated.

Waste from residues: Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues.

Unused products: This material and its container must be disposed of in a safe manner (see disposal instructions).

Contaminated packaging: Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty packaging materials should be recycled or disposed of in accordance with applicable regulations and practices.

SECTION 14:	TRANSPORTATION INFORMATION
--------------------	-----------------------------------

DOT: Not regulated as dangerous goods

IATA: Not regulated as dangerous goods.

IMDG: Not regulated as dangerous goods.



Linwood Mining & Minerals Corp.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code



SECTION 15:	REGULATORY INFORMATION
--------------------	-------------------------------

US federal regulations: This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D): Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4): Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA) Hazard categories:

- Immediate Hazard - No
- Delayed Hazard - Yes
- Fire Hazard - No
- Pressure Hazard - No
- Reactivity Hazard - No

SARA 302 Extremely hazardous substance: Not listed.

SARA 311/312 Hazardous chemical: Yes

SARA 313 (TRI reporting): Not regulated.

Other federal regulations:

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List: Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Not regulated.

Safe Drinking Water Act (SDWA): Not regulated



Linwood Mining & Minerals Corp.

US state regulations:

US. Massachusetts RTK - Substance List:

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

US. New Jersey Worker and Community Right-to-Know Act:

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

US. Pennsylvania Worker and Community Right-to-Know Law:

Crystalline Silica (Quartz) (CAS 14808-60-7)

Respirable Tridymite and Cristobalite (other forms of crystalline silica) (CAS Mixture)

US. Rhode Island RTK:

Not regulated.

US. California Proposition 65:

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT) - Listed substance:

Crystalline Silica (Quartz) (CAS 14808-60-7)

International Inventories:

<u>Country(s) or region</u>	<u>Inventory name</u>	<u>On inventory (yes/no)*</u>
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).



Prepared By: Linwood Mining and Minerals Corp.

Issue date 01/09/98

Revision date 10/24/19

Version #1

Disclaimer:

Linwood Mining and Minerals Corp. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person. Individuals receiving this information must consult their own technical and legal advisors and/ or exercise their own judgment in determining its appropriateness for a particular purpose. Linwood Mining and Minerals Corp makes no representations or warranties, either express or implied, including without limitation and warranties of merchantability or fitness for a particular purpose with respect to the information set forth herein or the product(s) to which the information refers. Accordingly, Linwood Mining and Minerals Corp will not be responsible or liable for any claims, losses or damages resulting from the use of or reliance upon or failure to use this information.