

SPECIFICATIONS


- 1. 4" Plain End inlet/outlet, 2" Plain End vents, H20 traffic-rated cast iron covers standard.
- 2. Liquid capacity: 500 gallons (66.8 cu. ft.).
- 3. Unit weight w/ standard cover: 460 lbs.
- 4. Maximum operating temperature 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- 5. Maximum burial depth: 106" from standard cover height.

ENGINEER SPECIFICATION GUIDE

Striem neutralization tank model LB-500 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 500 gallons. Covers shall be H20 traffic-rated pickable cast iron.



TOP VIEW



SECTION A-A

OPTIONS

Connection Options (Plain End Only)

Inlet / Outlet

- ☐ 6"
- ☐ 8"

Riser Options

From Factory: Up to 5"

- ☐ Up to 24": SR24 (2)
- ☐ Up to 39": LR24 (2)
- ☐ Up to 43": SR24 (4)
- ☐ Up to 58": SR24 (2)+ LR24 (2)
- ☐ Up to 72": LR24 (4)
- ☐ Up to 90": SR24 (2) + LR24 (4)
- ☐ Up to 106": LR24 (6)


- OR -

- ☐ CPRK (2): 11" - 106" (See specification for more detail.)

Additional Options

High Water Table Hold Down Kits (Choose One)

- ☐ HDK-13: With Steel Plates Included
- ☐ HDK-14: For Concrete Deadmen (By Others)
- ☐ C24-M (2): 2,000 lbs. Rated Bolted Composite Cover
- ☐ CC-1 & SPK: Command Center pH Monitoring Package with Sensor Placement Kit
- ☐ Limestone: 90%+ Calcium Carbonate (6,500 lbs.)



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

MODEL NUMBER: LB-500

DESCRIPTION:

LAB BASIN™
POLYETHYLENE NEUTRALIZATION TANK
500 GALLON CAPACITY

DWG BY: ENG DATE: 7/21/2026 REV: 3

SPECIFICATION SHEET

Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com

Made in the U.S.A

