

SPECIFICATIONS


- 1. 4" Plain End inlet/outlet, 3" Plain End vents, H20 traffic-rated cast iron cover standard.
- 2. Liquid capacity: 262 Gallons (35 cu. ft.).
- 3. Solids capacity: 145 Gallons (19.4 cu. ft.).
- 4. Flammable waste capacity: 105 Gallons (14 cu. ft.).
- 5. Unit weight w/ standard cover: 235 lbs.
- 6. Maximum operating temperature 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance
- 5. Diptubes are removable to inspect/clean piping
- 6. Minimum burial depth: 12"
- 7. Maximum burial depth: 90"

ENGINEER SPECIFICATION GUIDE

Striem flammable waste trap model FWT-35 shall be lifetime guaranteed and made in the USA. FWT-35 shall be constructed of polyethylene. FWT-35 shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. FWT-35 liquid holding capacity shall be 262 gallons and flammable waste capacity shall be 105 gallons. Solids capacity shall be 145 gallons. Cover shall be H20 traffic-rated pickable cast iron.




END VIEW




PO IS NON-CANCELABLE
ORDER IS NON-RETURNABLE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.



TOP VIEW



SECTION A-A

OPTIONS

Connection Options (Plain End Only)

Inlet / Outlet

6"

Riser Options

Minimum Burial Depth: 12"

- Up to 24": SR24
- Up to 39": LR24
- Up to 43": SR24 (2)
- Up to 58": SR24 + LR24
- Up to 72": LR24 (2)
- Up to 90": SR24 + LR24 (2)

- OR -

CPRK: 12" - 90" (See specification for more detail.)

Additional Options

- C24-M: 2,000 lbs. Rated Bolted Composite Cover
- HDK-10: High Water Table Hold Down Kit
- SS: Slick Stick™ Oil Level Monitoring System*

*Monitoring package will raise cover by 3"

SPECIFICATION SHEET

MODEL NUMBER: FWT-35

DESCRIPTION:
35 CUBIC FEET POLYETHYLENE
FLAMMABLE WASTE TRAP
UNRATED

DWG BY: ENG DATE: 7/21/2026 REV: 1

Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com

Made in the U.S.A

