SPECIFICATIONS

- 2" Plain End inlet, 3" Plain End vents, C24-H covers standard. 1.
- Oil capacity: 250 Gallons (33.4 cu ft). 2.
- 3. Unit weight w/ standard covers: 220 lbs.; w/ cast iron covers: 340 lbs.
- 4. Maximum operating temperature: 140°F continuous.

NOTES

- 1. For gravity drainage applications only.
- Do not use for pressure applications. 2.
- Narrow footprint allows clearance through doorways and down stairs. 3.
- 4. Cover placement allows full access to tank for proper maintenance

ENGINEER SPECIFICATION GUIDE

Striem oil collection tank model OCT-275 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Tank oil collection capacity shall be 250 gallons. Covers shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.

THIRD PARTY STRUCTURAL ANALYSIS

The OCT-275 has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.

Finished Grade

See options to determine available

dimension range


 \bigcirc


ANCHOR KIT

LIFT


NLET

INLET





END VIEW



	MODEL NUMBER:			
	DESCRIPTION:			
	250 GALLON POLYE OIL COLLECTIOI			
PROPRIETARY AND CONFIDENTIAL DINTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.	DWG BY:	ENG	DATE:	1/1