SPECIFICATIONS

- 2" Plain End inlet, 3" Plain End vents, C24-M cover standard. 1.
- 2. Oil capacity: 57 Gallons (7.6 cu ft).
- Unit weight w/ standard cover: 93 lbs.; w/ cast iron cover: 153 lbs. 3.
- 4. Maximum operating temperature: 140°F continuous.

NOTES

- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- Narrow footprint allows clearance through doorways and down stairs. 3.
- 4. Cover placement allows full access to tank for proper maintenance.

ENGINEER SPECIFICATION GUIDE


Striem oil collection tank model OCT-50 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank oil collection capacity shall be 57 gallons. Cover shall provide water/gas-tight seal and have a maximum 2,000 lbs. load capacity.


THIRD PARTY STRUCTURAL ANALYSIS

The OCT-50 has been structurally analyzed in accordance with the requirements of IBC 2012 and ASCE/SEI 7 for direct burial. The maximum burial depth and backfill material are specified in our installation instructions. The structural design has been reviewed and sealed by a professional engineer registered in the state of California. A sealed structural analysis report is available upon request.

> Finished Grade See options to determine available dimension range Ò

> > **END VIEW**





	MODEL NUMBER:		OCT-50		
	DESCRIPTION:				
PROPRIETARY AND CONFIDENTIAL	57 GALLON POLYETHYLENE OIL COLLECTION TANK				
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM , LLC . ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM , LLC . IS PROHIBITED.	DWG BY: ENG	DATE:	1/12/2024	REV:	1

Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A