## **SPECIFICATIONS**


- 1. 4" Plain End inlet/outlet, C24-H covers standard.
- 2. Max flow rate: 100 GPM.
- 3. Liquid capacity: 250 Gallons.
- 4. Solids capacity: 210 Gallons.
- 5. Unit weight w/ standard covers: 260 lbs.; w/ cast iron covers: 380 lbs.
- 6. Maximum operating temperature 140°F continuous.

## **NOTES**

- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Cover placement allows full access to tank for proper maintenance.
- 4. Narrow footprint allows clearance through doorways and down stairs.
- 5. Removable filter screen for easy maintenance.

## **ENGINEER SPECIFICATION GUIDE**


Striem solids interceptor model PS-275-S shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene. Interceptor shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Interceptor shall have corrosion-resistant removable filter screen with 1/4" perforations. Interceptor liquid holding capacity shall be 250 gallons and solids capacity shall be 210 gallons. Covers shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.




**TOP VIEW** 

## **Connection Options (Plain End Only)** Inlet / Outlet 4" □ 6" **Riser Options** From Factory: Up to 5" Up to 24": **SR24** (2) Up to 39": **LR24** (2) Up to 43": **SR24** (4) Up to 58": **SR24** (2) + **LR24** (2) Up to 72": **LR24** (4) Up to 90": **SR24** (2) + **LR24** (4) **Additional Options HDK-2:** High Water Anchor Kit C24-HP (2): H20 Rated Pickable Cast Iron Covers

**OPTIONS** 





**MODEL NUMBER: DESCRIPTION:** 

> POLYETHYLENE SCREEN STYLE **SOLIDS INTERCEPTOR** 250 LIQUID GALLON CAPACITY

**DWG BY:** ENG

DATE:

1/15/2024

**REV**:

2

PS-275-S

orders@striemco.com www.striemco.com



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

Striem Kansas City, KS Tel: 913-222-1500

Made in the U.S.A