
SPECIFICATIONS

STRIEM PWT-35


- 4" Plain End inlet/outlet, 3" Plain End vents, C24-H cover standard. 1.
- 2. Liquid capacity: 262 Gallons (35 cu. ft.).
- 3. Solids capacity: 145 Gallons (19.4 cu. ft.).
- Flammable waste capacity: 105 Gallons (14 cu. ft.). 4.
- Unit weight w/ standard cover: 175 lbs.; w/ cast iron cover: 235 lbs. 5.
- 6. Maximum operating temperature 140°F continuous.
- 7. Minimum burial depth: 12".

ENGINEER SPECIFICATION GUIDE


Striem flammable waste trap model FWT-35 shall be lifetime guaranteed and made in the USA. FWT-35 shall be constructed of polyethylene. FWT-35 shall be manufactured for above- or belowgrade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. FWT-35 liquid holding capacity shall be 262 gallons and flammable waste capacity shall be 105 gallons. Solids capacity shall be 145 gallons. Cover shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.



1



THE INFORMATION CONTAINED IN THIS DRAWING ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE V



	MODEL NU	JMBER:		FWT-35	
	DESCRIPTION: 35 CUBIC FEET POLYETHYLENE FLAMMABLE WASTE TRAP, UNRATED				
PROPRIETARY AND CONFIDENTIAL					
PROPRIE I ARY AND CONFIDENTIAL NTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. S A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.	DWG BY:	ENG	DATE:	6/4/2024	REV:

Made in the U.S.A