SPECIFICATIONS

- 1. 6" Plain End inlet/outlet shown, 3" Plain End vents standard.
- Liquid capacity: 500 gallons (67 cu. ft.).
 Unit weight: 800 lbs.
- 4. Maximum operating temperature 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Cover placement allows full access to tank for proper maintenance.
- 4. Lifting lug set for easy install.

ENGINEER SPECIFICATION GUIDE


Striem neutralization tank model LB-500 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 500 gallons. Cover shall provide water/gas-tight seal and have a maximum 16,000 lbs. load capacity.

THIRD PARTY STRUCTURAL ANALYSIS

The structural design of the LB-500 has been approved and stamped by a third-party structural engineer for direct burial in accordance with Striem's installation instructions.



TOP VIEW



	OPTIONS
	Connection Options (Plain End Only)
	Inlet / Outlet
	Riser Options From Factory: Up to 5" Up to 24": SR24 Up to 39": LR24 Up to 43": SR24 (2) Up to 58": SR24 + LR24 Up to 72": LR24 (2) Up to 90": SR24 + LR24 (2) Up to 106": LR24 (3) - OR - CPRK: 11" - 106" (See specification for more detail.) Additional Options SPK: Sensor Placement Kit*
	 HDK-8: High Water Table Hold Down Kit Limestone: 90%+ Calcium Carbonate (6,500 lbs.) *Required with CC-1
19" 52"¢ of Outlet	
LB-500 ASIN™ JTRALIZATION TANK J CAPACITY	SPECIFICATION SHEET Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com Made in the U.S.A

1