

SPECIFICATIONS


- 1. 6" Plain End inlet/outlet shown, 3" Plain End vents standard.
- 2. Max flow rate: 314 GPM.
- 3. Liquid capacity: 562 gallons (75 cu. ft.).
- 4. Oil capacity: 285 gallons.
- 5. Solids capacity: 162 gallons.
- 6. Unit weight: 1025 lbs.
- 7. Maximum operating temperature 140 °F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- 5. Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.

ENGINEER SPECIFICATION GUIDE


Striem oil separator model OT-500 shall be lifetime guaranteed and made in the USA. Separator shall be constructed of polyethylene with 7/8" nominal wall thickness. Separator shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Separator flow rate shall be 314 GPM. Separator liquid holding capacity shall be 562 gallons and oil capacity shall be 285 gallons. Solids capacity shall be 162 gallons. Covers shall be H20 rated pickable cast iron. Separator shall be certified to IAPMO IGC 183-2016 and carry a UPC listing.



SECTION B-B



TOP VIEW



SECTION A-A

OPTIONS

Connection Options (Plain End Only)

- Inlet / Outlet
 - ☐ 4"
 - ☐ 6"
 - ☐ 8"
- SELECTION REQUIRED

Riser Options

- From Factory: Up to 5"
 - ☐ Up to 24": SR24 (3)
 - ☐ Up to 39": LR24 (3)
 - ☐ Up to 43": SR24 (6)
 - ☐ Up to 58": SR24 (3) + LR24 (3)
 - ☐ Up to 72": LR24 (6)
 - ☐ Up to 90": SR24 (3) + LR24 (6)
 - ☐ Up to 106": LR24 (9)

- OR -

- ☐ CPRK (3): 11" - 106"
(See specification for more detail.)

Additional Options

- ☐ HDK-3: High Water Table Hold Down Kit
 - ☐ SS: Slick Stick™ Oil Level Monitoring System*
- *Monitoring system will raise covers by 3".

SPECIFICATION SHEET



MODEL NUMBER: OT-500

DESCRIPTION:

OIL TANKER™
POLYETHYLENE OIL SEPARATOR
562 GALLON CAPACITY

Striem
Kansas City, KS
Tel: 913-222-1500
orders@striemco.com
www.striemco.com

Made in the U.S.A



PO IS NON-CANCELABLE
ORDER IS NON-RETURNABLE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

DWG BY: ENG DATE: 1/23/2025 REV: 1