
SPECIFICATIONS 1. 6" Plain End inlet shown, 2" Plain End pump outlet, 3" Plain End vents, C24-HP covers standard. 2. Liquid holding capacity: 1500 gallons (201 cu. ft.). Unit weight w/ standard covers: 1676 lbs. 4. Maximum operating temperature 140°F continuous. 8"Ç **NOTES** of Vent-1. For gravity drainage applications only. 2. Do not use for pressure applications. 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to INLET unused vent location, or discarded if two chamber vents are required per local code. 4. Cover placement allows full access to tank for proper maintenance. Lifting lug set for easy install. 6. Maximum burial depth: 103" from standard cover height. **ENGINEER SPECIFICATION GUIDE** Striem decontamination tank model BB-1500-PP shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade


installation. Field-adjustable riser system is available as an

option to bring manhole covers to grade. Tank liquid


H20 rated pickable cast iron covers.


holding capacity shall be 1500 gallons. Covers shall be






OPTIONS





1/2" FPT conduit



PO IS NON-CANCELABLE **ORDER IS NON-**RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

BIO BASIN™ POLYETHYLENE DECONTAMINATION TANK WITH PUMP PLATE 1500 GALLONS CAPACITY

DWG BY: ENG

MODEL NUMBER:

DESCRIPTION:

DATE:

9/15/2025

REV:

3

BB-1500-PP

Made in the U.S.A

SPECIFICATION SHEET

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

