
SPECIFICATIONS 1. 6" Plain End inlet shown, 2" Plain End pump outlet, 3" Plain End vents, C24-HP cover standard. Liquid holding capacity: 500 gallons (66 cu. ft.). Unit weight w/ standard cover: 860 lbs. 4. Maximum operating temperature 140°F continuous.


- **NOTES**
- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- Lifting lug set for easy install.
- 6. Maximum burial depth: 103" from standard cover height.


ENGINEER SPECIFICATION GUIDE

Striem decontamination tank model BB-500-PP shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 500 gallons. Cover shall be H20 rated pickable cast iron.




TOP VIEW





SECTION B-B



CANCELABLE RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

PO IS NON-**ORDER IS NON-**

BIO BASIN™ POLYETHYLENE DECONTAMINATION TANK WITH PUMP PLATE **500 GALLON CAPACITY**

DWG BY: ENG

MODEL NUMBER:

DESCRIPTION:

DATE:

9/15/2025

BB-500-PP

REV: 3

SPECIFICATION SHEET

OPTIONS

SELECTION

REQUIRED

CPRK: 11" - 103" (See specification for more detail.)

C24-M: 2,000 lbs. Rated Bolted Composite Cover

HDK-8: High Water Table Hold Down Kit

AVA-3: Single-Level Monitoring Package AVA-4: Multi-Level Monitoring Package

Connection Options (Plain End Only)

Inlet

3"

□ 6"

- OR -

Riser Options

From Factory: 0" - 2"

Up to 21": SR24

☐ Up to 36": **LR24**

Up to 40": **SR24** (2)

Up to 69": **LR24** (2)

Up to 103": **LR24** (3)

Additional Options

Up to 55": SR24 + LR24

Up to 87": **SR24** + **LR24** (2)

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A

