#### **SPECIFICATIONS**


- 6" Plain End inlet shown, 3" Plain End vents, C24-HP cover standard.
- Liquid holding capacity: 500 gallons (66 cu. ft.).
- Unit weight w/ standard cover: 860 lbs.
- 4. Maximum operating temperature 140°F continuous.

### **NOTES**

- For gravity drainage applications only.
- 2. Do not use for pressure applications.
- Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- Cover placement allows full access to tank for proper maintenance.
- Lifting lug set for easy install.
- Maximum burial depth: 106" from standard cover height.

#### **ENGINEER SPECIFICATION GUIDE**


Striem decontamination tank model BB-500 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustabe riser system is available as an option to bring manhole cover to grade. Tank liquid holding capacity shall be 500 gallons. Cover shall be H20 rated pickable cast iron.



**TOP VIEW** 

# Finished Grade See options to determine available dimension range Ø61-3/4" O.D. Ø 60" I.D. 55"Q of Vents

**SECTION B-B** 




PO IS NON-CANCELABLE **ORDER IS NON-**RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.



**SECTION A-A** 

## **SPECIFICATION SHEET**

**OPTIONS** 

CPRK: 11" - 106" (See specification for more detail.)

C24-M: 2,000 lbs. Rated Bolted Composite Cover

**HDK-8:** High Water Table Hold Down Kit

AVA-3: Single-Level Monitoring Package \* AVA-4: Multi-Level Monitoring Package \*

\*Monitoring packages will raise covers by 3".

SELECTION

REQUIRED

**Optional Outlet** 

**3**"

**4"** 

6"

Inlet

**3**"

□ 6"

- OR -

**Riser Options** 

From Factory: 0" - 5"

☐ Up to 24": **SR24** 

☐ Up to 39": **LR24** 

Up to 43": **SR24** (2)

Up to 72": **LR24** (2)

Up to 106": **LR24** (3)

**Additional Options** 

Up to 58": SR24 + LR24

☐ Up to 90": **SR24** + **LR24** (2)

BIO BASIN™ POLYETHYLENE DECONTAMINATION TANK **500 GALLON CAPACITY** 

Striem **Kansas City, KS** Tel: 913-222-1500 orders@striemco.com www.striemco.com



**DWG BY:** ENG

**MODEL NUMBER:** 

**DESCRIPTION:** 

DATE:

9/15/2025

BB-500

**REV**: 2 Made in the U.S.A