#### **SPECIFICATIONS**


- 1. 6" Plain End inlet/outlet shown, 3" Plain End vents, C24-HP cover standard.
- Liquid capacity: 500 gallons (66 cu. ft.).
   Solids capacity: 400 gallons.
- 4. Unit weight w/ standard cover: 860 lbs.
- 5. Maximum operating temperature 140°F continuous.


#### **NOTES**


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.


#### **ENGINEER SPECIFICATION GUIDE**


Striem solids interceptor model CB-500-S shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene with 7/8" nominal wall thickness. Interceptor shall be manufactured for below-grade installation. Fieldadjustable riser system is available as an option to bring manhole cover to grade. Interceptor liquid holding capacity shall be 500 gallons and solids capacity shall be 400 gallons. Cover shall be H20 rated pickable cast iron.












### **SECTION B-B**



PO IS NON-CANCELABLE **ORDER IS NON-**

RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

## POLYETHYLENE CATCH BASIN **500 GALLON CAPACITY**

**DWG BY: ENG** 

**MODEL NUMBER:** 

**DESCRIPTION:** 

DATE:

9/15/2025

CB-500-S

**REV**:

# **SPECIFICATION SHEET**

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A

