SPECIFICATIONS 1. 6" Plain End inlet/outlet shown, 3" Plain End vents,


- C24-HP covers standard.
- 2. Liquid capacity: 750 gallons (100 cu. ft.).
- 3. Solids capacity: 295 gallons.
- 4. Unit weight w/ standard covers: 1253 lbs.
- 5. Maximum operating temperature 140°F continuous.

NOTES


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- 5. Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.


ENGINEER SPECIFICATION GUIDE


Striem solids interceptor model CB-750-S shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene with 7/8" nominal wall thickness. Interceptor shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Interceptor liquid holding capacity shall be 750 gallons and solids capacity shall be 295 gallons. Covers shall be H20 rated pickable cast iron.




TOP VIEW







SECTION B-B



PO IS NON-CANCELABLE **ORDER IS NON-**RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

SECTION A-A

MODEL NUMBER:

DESCRIPTION: POLYETHYLENE CATCH BASIN

750 GALLON CAPACITY

DWG BY: ENG

DATE:

9/15/2025

CB-750-S

REV: 2

SPECIFICATION SHEET

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A

