## **SPECIFICATIONS**


- 1. 4" Plain End inlet/outlet, 2" Plain End vents, C24-HP covers standard.
- 2. Liquid holding capacity: 250 Gallons.
- 3. Unit weight w/ standard covers: 345 lbs.
- 4. Maximum operating temperature 140°F continuous.


## **NOTES**


- 1. For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- Diptube is removable to inspect/clean piping.
- 6. Maximum burial depth: 90" from standard cover height.


## **ENGINEER SPECIFICATION GUIDE**

Striem neutralization tank model LB-275 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene. Tank shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Tank liquid holding capacity shall be 250 gallons. Covers shall be H20 rated pickable cast iron.











**MODEL NUMBER: DESCRIPTION:** 

> LAB BASIN™ POLYETHYLENE NEUTRALIZATION TANK

LB-275

**DWG BY:** ENG DATE:

9/16/2025

**REV**:

2

## **SPECIFICATION SHEET**

**OPTIONS** 

☐ CPRK (2): 11" - 90" (See specification for more detail.)

C24-M (2): 2,000 lbs. Rated Bolted Composite Covers

**Limestone:** 90%+ Calcium Carbonate (3,150 lbs.)

☐ **HDK-2**: High Water Table Hold Down Kit

Package with Sensor Placement Kit

☐ CC-1 & SPK: Command Center pH Monitoring

**Connection Options (Plain End Only)** 

Inlet / Outlet

**Riser Options** 

From Factory: Up to 5"

☐ Up to 24": **SR24** (2)

Up to 39": **LR24** (2)

Up to 43": **SR24** (4)

Up to 72": **LR24** (4)

**Additional Options** 

☐ Up to 58": **SR24** (2) + **LR24** (2)

☐ Up to 90": **SR24** (2) + **LR24** (4)

**4"** □ 6"

- OR -

**Striem** Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.