SPECIFICATIONS


- 1. 6" Plain End inlet/outlet shown, 3" Plain End vents, C24-HP covers standard.
- Liquid capacity: 750 gallons (100 cu. ft.).
- Unit weight: 1210 lbs.
- 4. Maximum operating temperature 140°F continuous.


NOTES


- For gravity drainage applications only.
- 2. Do not use for pressure applications.
- 3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
- 4. Cover placement allows full access to tank for proper maintenance.
- Lifting lug set for easy install.
- 6. Maximum burial depth: 106" from standard cover height.

ENGINEER SPECIFICATION GUIDE

Striem neutralization tank model LB-750 shall be lifetime guaranteed and made in the USA. Tank shall be constructed of polyethylene with 7/8" nominal wall thickness. Tank shall be manufactured for below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Tank liquid holding capacity shall be 750 gallons. Covers shall be H20 rated pickable cast iron.







PO IS NON-CANCELABLE **ORDER IS NON-**RETURNABLE

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC.

ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

LAB BASIN™ POLYETHYLENE NEUTRALIZATION TANK 750 GALLON CAPACITY

DWG BY: ENG

MODEL NUMBER:

DESCRIPTION:

DATE:

9/16/2025

LB-750

REV: 2 **SPECIFICATION SHEET**

OPTIONS

CPRK (3): 11" - 106" (See specification for more detail.)

C24-M (3): 2,000 lbs. Rated Bolted Composite Covers

Limestone: 90%+ Calcium Carbonate (9,800 lbs.)

☐ CC-1 & SPK: Command Center pH Monitoring

HDK-4: High Water Table Hold Down Kit

Package with Sensor Placement Kit

SELECTION

REQUIRED

Connection Options (Plain End Only)

Inlet / Outlet

Riser Options

From Factory: Up to 5"

Up to 24": **SR24** (3)

Up to 39": **LR24** (3)

Up to 43": **SR24** (6)

Up to 72": **LR24** (6)

☐ Up to 106": **LR24** (9)

Additional Options

Up to 58": **SR24** (3) + **LR24** (3)

☐ Up to 90": **SR24** (3) + **LR24** (6)

4"

6"

- OR -

Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com

Made in the U.S.A

