




1. 4" Plain End inlet/outlet, 3" Plain End vents, C24-HP covers standard.
2. Liquid capacity: 500 Gallons (66.8 cu. ft.).
3. Flammable Liquid capacity: 275 Gallons.
4. Solids capacity: 164 Gallons.
5. Unit weight w/ standard covers: 456 lbs.
6. Maximum operating temperature 140°F continuous.

1. For gravity drainage applications only.
2. Do not use for pressure applications.
3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
4. Cover placement allows full access to tank for proper maintenance.
5. Diptubes are removable to inspect/clean piping.
6. Maximum burial depth: 106" from standard cover height.

Striem flammable liquid interceptor model FLI-500 shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene. Interceptor shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Interceptor liquid holding capacity shall be 500 gallons and flammable liquid capacity shall be 275 gallons. Solids capacity shall be 164 gallons. Covers shall be H20 rated pickable cast iron.



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF **STRIEM, LLC**.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF **STRIEM, LLC** IS PROHIBITED.

MODEL NUMBER: FLI-500		SPECIFICATION SHEET	
DESCRIPTION: 500 GALLON POLYETHYLENE FLAMMABLE LIQUID INTERCEPTOR, UNRATED		Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com Made in the U.S.A	
DWG BY: ENG	DATE: 12/5/2025	REV: 3	