

SPECIFICATIONS


1. 4" Plain End inlet/outlet, H20 traffic-rated cast iron cover standard.
2. Liquid capacity: 110 Gallons.
3. Solids capacity: 70 Gallons.
4. Unit weight w/ standard cover: 180 lbs.
5. Maximum operating temperature 140°F continuous.

NOTES

1. For gravity drainage applications only.
2. Do not use for pressure applications.
3. Cover placement allows full access to tank for proper maintenance.
4. Narrow footprint allows clearance through doorways and down stairs.
5. Diptube is removable to inspect or clean piping.
6. Maximum burial depth: 72" from standard cover height.

ENGINEER SPECIFICATION GUIDE

Striem solids interceptor model CB-125-S shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene. Interceptor shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole cover to grade. Interceptor liquid holding capacity shall be 110 gallons and solids capacity shall be 70 gallons. Cover shall be H20 traffic-rated pickable cast iron.



TOP VIEW

OPTIONS

Connection Options (Plain End Only)

Inlet / Outlet

- 4"
- 6"

Riser Options

From Factory: Up to 5"


- Up to 24": **SR24**
- Up to 39": **LR24**
- Up to 43": **SR24 (2)**
- Up to 58": **SR24 + LR24**
- Up to 72": **LR24 (2)**

- OR -


- CPRK: 11" - 72"** (See specification for more detail.)

Additional Options


- C24-M: 2,000 lbs. Rated Bolted Composite Cover**
- HDK-2: High Water Table Hold Down Kit**



END VIEW



SECTION A-A



PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

MODEL NUMBER: CB-125-S		SPECIFICATION SHEET	
DESCRIPTION: POLYETHYLENE CATCH BASIN			
DWG BY: ENG	DATE: 2/23/2026	REV: 1	Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com Made in the U.S.A