

SPECIFICATIONS


1. 4" Plain End inlet/outlet, 3" Plain End vents, H20 traffic-rated cast iron covers standard.
2. Liquid capacity: 262 gallons (35 cu.ft.).
3. Solids capacity: 95 gallons.
4. Flammable liquid capacity: 144 gallons.
5. Unit weight w/ standard covers: 345 lbs.
6. Maximum operating temperature 140°F continuous.

NOTES

1. For gravity drainage applications only.
2. Do not use for pressure applications.
3. Capped auxiliary vent provided to allow flexibility with vent piping and design. Provided cap can be moved to unused vent location, or discarded if two chamber vents are required per local code.
4. Cover placement allows full access to tank for proper maintenance.
5. Narrow footprint allows clearance through doorways and down stairs.
6. Diptubes are removable to inspect/clean piping.
7. Maximum burial depth: 90" from standard cover height.


ENGINEER SPECIFICATION GUIDE

Striem flammable liquid interceptor model FLI-275 shall be lifetime guaranteed and made in the USA. Interceptor shall be constructed of polyethylene. Interceptor shall be manufactured for above- or below-grade installation. Field-adjustable riser system is available as an option to bring manhole covers to grade. Interceptor liquid holding capacity shall be 262 gallons and flammable liquid capacity shall be 144 gallons. Solids capacity shall be 95 gallons. Covers shall be H20 traffic-rated pickable cast iron.




TOP VIEW


OPTIONS	
Connection Options (Plain End Only)	
Inlet / Outlet	
<input type="checkbox"/>	4"
<input type="checkbox"/>	6"
Riser Options	
From Factory: Up to 5"	
<input type="checkbox"/>	Up to 24": SR24 (2)
<input type="checkbox"/>	Up to 39": LR24 (2)
<input type="checkbox"/>	Up to 43": SR24 (4)
<input type="checkbox"/>	Up to 58": SR24 (2) + LR24 (2)
<input type="checkbox"/>	Up to 72": LR24 (4)
<input type="checkbox"/>	Up to 90": SR24 (2) + LR24 (4)
- OR -	
<input type="checkbox"/>	CPRK (2): 11" - 90" (See specification for more detail.)
Additional Options	
<input type="checkbox"/>	C24-M (2): 2,000 lbs. Rated Bolted Composite Covers
<input type="checkbox"/>	HDK-2 : High Water Table Hold Down Kit
<input type="checkbox"/>	SS : Slick Stick™ Oil Level Monitoring Solution**
**Monitoring system will raise covers by 3"	



SECTION B-B



SECTION A-A



PO IS NON-CANCELABLE ORDER IS NON-RETURNABLE

PROPRIETARY AND CONFIDENTIAL
THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF STRIEM, LLC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF STRIEM, LLC. IS PROHIBITED.

MODEL NUMBER: FLI-275	
DESCRIPTION: 262 GALLON POLYETHYLENE FLAMMABLE LIQUID INTERCEPTOR, UNRATED	
DWG BY: ENG	DATE: 3/3/2026
REV: 2	

SPECIFICATION SHEET	
Striem Kansas City, KS Tel: 913-222-1500 orders@striemco.com www.striemco.com	
Made in the U.S.A	